



R134a : H/MBP 220/240-1-50 - Model with capillary tube and valves													
Model	Power	Liquid receiver capacity	Dimensions			Cooling power					Connections		Motor
	HP		W	D	H	Watt. Te = (°C)					suction	Liq.	
		dm ³	mm	mm	mm	-15	-10	-5	0	5	inch	inch	
EMT6144Z-1C	1/5	0,6	431	306	226	221	280	349	431	523	3/8"	1/4"	CSIR
EMT6160Z-1C	1/4	1,1	435	306	254	297	373	465	571	692	3/8"	1/4"	CSIR
EMT6170Z-1C	1/3	1,1	435	306	254	318	402	502	617	749	3/8"	1/4"	CSIR
NEK6187Z-1C	1/3	1,1	467	339	296	359	457	574	711	870	3/8"	1/4"	CSIR
NEK6214Z-1C	1/2	1	467	339	296	584	750	935	1139	1368	3/8"	1/4"	CSIR
T6215Z-1C	1/2+	1,2	465	340	296	625	775	942	1135	1335	3/8"	1/4"	CSIR

R134a : H/MBP 220/240-1-50 - Model with valve, liquid receiver and Castel valves													
Model	Power	Liquid receiver capacity	Dimensions			Cooling power					Connections		Motor
	HP		W	D	H	Watt. Te = (°C)					Suc-tion	Liq.	
		dm ³	mm	mm	mm	-15	-10	-5	0	5	inch	inch	
EMT6144Z-2C	1/5	0,6	431	306	226	221	280	349	431	523	3/8"	1/4"	CSIR
EMT6160Z-2C	1/4	1,1	435	306	254	297	373	465	571	692	3/8"	1/4"	CSIR
EMT6170Z-2C	1/3	1,1	435	306	254	318	402	5'2	617	749	3/8"	1/4"	CSIR
NEK6187Z-2C	1/3	1,1	467	339	296	481	600	737	894	1070	3/8"	1/4"	CSIR
NEK6214Z-2C	1/2+	1,1	467	339	296	658	826	1004	1192	1395	3/8"	1/4"	CSIR
NT6215Z-2C	1/2+	1,2	465	340	296	625	775	942	1135	1335	3/8"	1/4"	CSIR
NJ6220Z-2C	3/4	2,3	481	409	324	1011	1259	1537	1849	2193	1/2"	3/8"	CSIR
NJ6226Z-2C	1+	2,3	481	409	324	1372	1686	2035	2419	2814	5/8"	3/8"	CSR

R134a : H/MBP 380/420-3-50 - Model with valve, liquid receiver and Castel valves													
Model	Power	Liquid receiver capacity	Dimensions			Cooling power					Connections		Motor
	HP		W	D	H	Watt. Te = (°C)					Suction	Liq.	
		dm ³	mm	mm	mm	-15	-10	-5	0	5	inch	inch	
NJ6220ZX-2C	3/4	2,3	481	409	324	994	1256	1529	1843	2154	1/2"	3/8"	3 phase

Ta = Ambient Temperature, gas 32°C

Standard supply: interception valve, inert gas charge

1 = capillary tube

2 = Capillary tube/valve

2V = condensation with two fans



R404A - R507 : H/MBP 220/240-1-50 - Model with capillary tube and valves													
Model	Power	Liquid receiver capacity	Dimensions			Cooling power					Connections		Motor
	HP		W	D	H	Watt. Te = (°C)					suction	Liq.	
		dm ³	mm	mm	mm	-15	-10	-5	0	5	inch	inch	
EMT6144GK-1C	1/5	0,6	431	306	226	300	363	438	519	603	3/8"	1/4"	CSIR
EMT6165GK-1C	1/4	1,1	435	306	254	395	477	583	697	799	3/8"	1/4"	CSIR
NEK6181GK-1C	1/2-	1,1	467	339	296	470	585	715	860	1020	3/8"	1/4"	CSIR
NEK6210GK-1C	1/2	1,1	467	339	296	594	604	826	986	1204	3/8"	1/4"	CSIR
NEK6213GK-1C	1/2+	1,1	467	339	296	802	996	1130	1292	1439	3/8"	1/4"	CSIR

R404A - R507 : H/MBP 220/240-1-50 - Model with valve, liquid receiver and Castel valves													
Model	Power	Liquid receiver capacity	Dimensions			Cooling power					Connections		Motor
	HP		W	D	H	Watt. Te = (°C)					suction	Liq.	
		dm ³	mm	mm	mm	-15	-10	-5	0	5	inch	inch	
EMT6144GK-2C	1/5	0,6	431	306	226	300	363	438	519	603	3/8"	1/4"	CSIR
EMT6165GK-2C	1/4	1,1	435	306	254	395	477	583	697	799	3/8"	1/4"	CSIR
NEK6181GK-2C	1/2-	1,1	467	339	296	470	585	715	860	1020	3/8"	1/4"	CSIR
NEK6210GK-2C	1/2	1,1	467	339	296	670	665	886	1032	1228	3/8"	1/4"	CSIR
NEK6213GK-2C	1/2+	1,1	467	339	296	802	966	1130	1292	1439	3/8"	1/4"	CSIR
NEK6213GK-2V2C	1/2+	1,1	440	609	260	904	1064	1213	1352	1468	3/8"	1/4"	CSIR
NEK6217GK-2C	3/4	2,3	470	395	324	960	1180	1406	1640	1880	3/8"	3/8"	CSR
NEK6217GK-2V2C	3/4	2,3	440	613	295	960	1180	1406	1640	1880	3/8"	3/8"	CSR
NT6220GK-2C	3/4+	2,3	518	395	324	1008	1246	1503	1776	2070	1/2"	3/8"	CSR
NT6220GK-2V2C	3/4+	2,3	440	787	293	1008	1246	1503	1776	2070	1/2"	3/8"	CSR
NT6222GK-2C	1-	2,3	518	395	324	1122	1389	1679	1986	2316	1/2"	3/8"	CSR
NT6226GK-2C	1+	2,3	500	405	390	1568	1878	2198	2526	2864	1/2"	3/8"	CSR
NT6226GK-2V2C	1+	2,3	461	787	293	1568	1878	2198	2526	2864	1/2"	3/8"	CSR
NJ9232GK-2C	1.1/4	3,9	600	440	379	1764	2124	2512	2898	3294	5/8"	1/2"	CSR
NJ9232GK-2V2C	1.1/4	3,9	461	787	331	1764	2124	2512	2898	3294	5/8"	1/2"	CSR
NJ9238GK-2V2G	1.1/2+	3,9	461	787	331	2147	2560	3157	3434	3895	5/8"	1/2"	CSR

Ta = Ambient Temperature, gas 32°C

Standard supply: interception valve, inert gas charge

1 = capillary tube

2 = Capillary tube/valve

2V = condensation with two fans



R404A - R507 : H/MBP 380/420-3-50 - Model with valve, liquid receiver and Castel valves													
Model	Power	Liquid receiver capacity	Dimensions			Cooling power					Connections		Motor
	HP		W	D	H	Watt. Te = (°C)					suction	Liq.	
		dm ³	mm	mm	mm	-15	-10	-5	0	5	inch	inch	
NJ9226GS-2C	1	2,3	512	410	390	1523	1822	2094	2364	2616	5/8"	3/8"	3 PHASE
NJ9226GS-2V2C	1	2,3	491	787	328	1523	1822	2094	2364	2616	5/8"	3/8"	3 PHASE
NJ9232GS-2V2C	1.1/4	3,9	491	787	328	1855	2219	2550	2879	3186	5/8"	1/2"	3 PHASE
NJ9238GS-2C	1.1/2+	3,9	600	440	379	2268	2685	3134	3638	4172	5/8"	1/2"	3 PHASE
NJ9238GS-2V2C	1.1/2+	2,3	491	787	328	2268	2685	3117	3585	4021	5/8"	1/2"	3 PHASE

R404A - R507 : LBP 220/240-1-50 - Model with valve, liquid receiver and Castel valves													
Model	Power	Liquid receiver capacity	Dimensions			Cooling power					Connections		Motor
	HP		W	D	H	Watt. Te = (°C)					suction	Liq.	
		dm ³	mm	mm	mm	-30	-25	-20	-15	-10	inch	inch	
NEK2134GK-2C	1/2+	1,1	467	339	296	337	456	593	733	884	3/8"	1/4"	CSIR
NEK2150GK-2C	3/4	1,1	467	339	296	474	569	683	817	969	3/8"	1/4"	CSIR
NEK2168GK-2C	1+	1,2	467	340	296	484	643	825	994	1153	3/8"	1/4"	CSR
NT2178GK-2C	1.1/4	1,2	467	340	296	542	710	912	1164	1455	3/8"	1/4"	CSR
NT2192GK-2C	1.1/2	2,3	481	409	324	691	896	1142	1443	1787	1/2"	3/8"	CSR
NJ2212GK-2C	2	2,3	481	409	324	962	1251	1574	1950	2365	5/8"	3/8"	CSR
NJ2212GK-2V2C	2	2,3	440	440	312	962	1251	1574	1950	2365	5/8"	3/8"	CSR

R404A - R507 : LBP 380/420-3-50 - Model with valve, liquid receiver and Castel valves													
Model	Power	Liquid receiver capacity	Dimensions			Cooling power					Connections		Motor
	HP		W	D	H	Watt. Te = (°C)					suction	Liq.	
		dm ³	mm	mm	mm	-30	-25	-20	-15	-10	inch	inch	
NJ2212GS-2C	2+	2,3	481	409	324	1163	1479	1826	2198	2605	5/8"	3/8"	3 PHASE

Ta = Ambient Temperature, gas 32°C

Standard supply: interception valve, inert gas charge

1 = capillary tube

2 = Capillary tube/valve

2V = condensation with two fans